



M A R L I Q U E<sup>™</sup>  
M A R B L E  
BY COSENTINO

## What is Marlique Marble?

Marlique Marble by Cosentino is an engineered marble for vanities, shower walls, tub decks—virtually any bathroom surface. Marlique is made up of 93 percent marble and seven percent polyester resin and pigments, making it more durable, consistent and dependable than quarried or cultured marble. Marlique Marble is a tremendously versatile surfacing product; affordable yet beautiful... and is available in exquisite colors that will fit most individual styles and tastes.

## Benefits

- Low liquid absorption rate
- More resistant to scratches and stains than quarried or cultured marble
- Carries a 10-year warranty on manufacturing defects

CHARACTERISTICS	METHOD	RESULTS
Density	DIN 52102 ASTM C 97	2.40 - 2.50 gr/cm <sup>3</sup>
Water absorption	DIN 52103 EN 99, ASTM C 97 BS 6431 part 11	< 0.1% < 0.20%
Flexural strength	DIN 52112 EN 100, ASTM C 99 BS 6431 part 12	2,600 - 4,300 psi 2,900 - 5,100 psi
Compressive strength	DIN 52105 ASTM C 170	16,000 - 22,000 psi
Surface scratch hardness	EN 101 BS 6431 part 13	3 - 4*
Resistance to deep abrasion	DIN 52108 ASTM C 241 EN 102 - BS 6431 part 14	13.6 cm <sup>3</sup> /50 20 - 32 cm <sup>2</sup> /index 250 -393 num <sup>3</sup>
Static coefficient of friction (antislip)	ASTM C 1028 (Neolite: Dry/Wet)	polished 0.78 - 0.47
Frost resistance	DIN 52104 - A Teil 1	complies with the standards
Combustion reaction	DIN 4102 Teil 1	B1

## Marlique Marble Technical Specifications

Following are the size, thickness and edge choices of Marlique Marble.

- 1.2cm slab – 48-7/16”x120”
- 2cm slab – 48-7/16”x120”
- 3cm slab – 48-7/16”x120”
- 12”x12” tile with straight edge
- 12”x12” tile with beveled edge
- Shower walls come in 1.2cm (7/16”) thickness
- Vanity tops and tub decks are available in 2cm (3/4”) thickness

## Care & Maintenance

- To clean Marlique Marble, you need only a damp cloth or paper towel.
- In case of stubborn spots, a small amount of liquid detergent is sufficient.
- For extremely difficult stains, mild household cleaners such as Formula 409® or Lysol® may be used without damaging the countertop. All hazy residue must be completely rinsed off to avoid diminishing the shine and beauty of the surface.
- Sealing your Marlique surface once a year will suffice; any marble sealer available will do. Follow the product’s manufacturer’s instructions when applying.

## Caution:

- *No surface is indestructible.* As with any surface, Marlique Marble can be damaged by exposure to acid chemicals and some solvents.
- Do not use products containing trichlorethane or methylene chloride, such as paint removers or furniture strippers.
- Avoid chemicals containing high acidity (low pH levels) and organic acids.
- In the event of accidental exposure to any of these damaging products, thoroughly rinse with water as soon as possible.

## Warranty Information

Cosentino USA offers a limited manufacturer’s warranty to the original owners of installed Marlique Marble products that for a period of 10 years from the date of installation the material will be free from manufacturing defects. As more fully set forth in the complete limited warranty, please be aware that there are certain instances where this limited warranty does not apply, such as—although not limited to—color variances, thermal shock, chemical abuse or defects caused by misuse. Please see the complete limited warranty for additional information.

For more information please call us at 1.877.marlique or visit our website at [www.marliquemarble.com](http://www.marliquemarble.com)



1 . 8 7 7 . M A R L I Q U E  
W W W . M A R L I Q U E M A R B L E . C O M